

Spesifikasi Produk

Product Datasheet

DATS 125/4

Automatic Transfer Switch

Gambar Produk

Product Picture



Karakteristik Produk

Product Characteristics

Kategori Produk Product Category	Automatic Transfer Switch
Nama Produk Product Name	DATS 125/4
Arus (A) Current Rate	125 A
Pelat Nama Legend Plate	I - O - II
Pole	4 Pole
Rating Tahanan Isolasi Voltase Rated Insulation Withstand Voltage	500 V
Rating Tahanan Impulsif Voltase Rated Impulsive Wuthstand Voltage	8 kV
Rating Hubungan Pendek Tahanan Waktu Rated Short Time Withstand	5 KA
Waktu Transfer Transfer Time	≤ 5 s
Kontrol Suplai Voltase Control Supply Voltage	AC 220 V
Suhu Operasional Operational Temperature	0° C - 40° C (No Condensation)
Suhu Kelembaban Relative Humidity	95%

Karakteristik Teknik

Technical Characteristics

Struktur Produk Product Structure	Memiliki ukuran kecil, struktur sederhana. Switching driven didorong menggunakan motor tunggal Has a small size, simple structure. Switching driven is driven by single motor
Material Struktur Fisik Structure Material Body	Automatic Transfer Switch terdiri dari kerangka utama dengan perangkat luar yang terbuat dari serat kaca, unsaturated resin poliester, motor mikro, multi stage, peredam kecepatan, perangkat kontrol SCM The automatic transfer switch is composed of the main body with enclosure made of glass fiber unsaturated polyester resin,micro motor,multi stage,speed reducer,SCM control device

Fungsi Pengoprasian	Manual handle operating, Manual remote control operating, Automatic control operating
The opersting Function	Pengoperasian pegangan manual, Pengoperasian remote control manual, Pengoperasian kontrol otomatis
Warna	Hitam
Colour	Black
Standar	IEC60947-6-1
Standards	
Berat Bersih	8750 g
Net Weight	8750 g

Kemasan

Packing

Jenis Unit Kemasan 1	PC
Unit Type in Package 1	PC
Jumlah Unit Kemasan 1	1
Unit Quantity in Package 1	1
Berat Kemasan 1	8750 g
Package 1 Weight	8750 g
Tinggi Kemasan 1	205 mm
Package 1 Height	205 mm
Lebar Kemasan 1	290 mm
Package 1 Width	290 mm
Panjang Kemasan 1	170 mm
Package 1 Length	170 mm