

## Spesifikasi Produk

Product Datasheet

## DVM -1

Phase Failure Relay

### Gambar Produk

Product Picture



### Karakteristik Produk

Product Characteristics

<b>Kategori Produk</b> Product Category	Universal Relay & Socket
<b>Nama Produk</b> Product Name	DVM-1
<b>Dimensi</b> Dimension	61 x 49 x 70 mm
<b>Arus (A)</b> Current Rate	10 A
<b>Tegangan</b> Voltage Rate	380 VAC
<b>Phasa</b> Phase	3
<b>Daya</b> Power Consumption	≤ 2 VA
<b>Ketahanan Mekanis</b> Operation Life	Mechanical : 5.000.000 Electrical: 50.000
<b>Resistensi Kontak</b> Contact resistance	≤ 100 M Ω
<b>Resistensi Insulasi</b> Insulation resistance	≥ 100 M Ω
<b>Tekanan Kontak</b> Contact Pressure	AC 1000 V
<b>Kapasitas Beban Kontak</b> Contact Load Capacity	AC 200 V 10 A
<b>Frekuensi</b> Frequency	50/60 Hz
<b>Suhu Operasional</b> Operational Temperature	-10° C ~ + 55° C (No Condensation)
<b>Suhu Kelembaban</b> Relative Humidity	45 - 85 % RH
<b>Pemasangan</b> Mounting	Socket mount with PF083A
<b>Fungsi</b> Function	Prevent reverse run of 3 phase motor : surge absorber, prevent high voltage : phase sequence and Phase lack Protection Function
<b>Struktur Model</b> Model Structure	Product has advantages of flexible control strong, anti - interference performance, low power consumption, large contact capacity, and wide voltage range
<b>Warna</b> Colour	Hitam Black
<b>Berat Bersih</b> Net Weight	244 g 244 g

### Kemasan

Packing

<b>Jenis Unit Kemasan 1</b> Unit Type in Package 1	PC PC
<b>Jumlah Unit Kemasan 1</b> Unit Quantity in Package 1	1 1
<b>Berat Kemasan 1</b> Package 1 Weight	244 g 244 g
<b>Tinggi Kemasan 1</b> Package 1 Height	70 mm 70 mm
<b>Lebar Kemasan 1</b> Package 1 Width	100 mm 100 mm
<b>Panjang Kemasan 1</b> Package 1 Length	80 mm 80 mm